



Equipment

Vacuums

- Insul-Vac 8
- Versa-Vac 13
- Versa-Vac 15

Accessories & Additional Info

- Accessories
- Product Information
- Links

INSULATION REMOVAL MACHINES – VERSA-VAC 15

Insulation Removal Vacuum – Versa-Vac 15 – Top Of The Line 15 HP Workhorse
 When you need the most power and handling capacity you can get to take care of the toughest and messiest jobs, the Versa-Vac 15 is your best choice. The Versa-Vac 15 insulation removal vacuum is designed for the fastest, most profitable removal of fire, smoke and water damaged insulation from attics, sidewalls and crawl spaces.

Versa-Vac 15 features:

- | 15 HP Kohler OHV motor
- | Cellulose processing capacity of 4347 cu. ft./hr., 6042 lbs./hr.
- | Fiberglass processing capacity of 5849 cu. ft./hr., 4199 lbs./hr.



Handle Bulky Insulation Materials Efficiently & Productively

Blown-in insulation and plaster chips – wet or dry – are removed quickly and efficiently. Material intended for recycling can be conveyed directly to your spraying machine for reuse. Waste material can be discharged directly into 75 cubic foot disposable collection bags or directly into a Dumpster® receptacle.

Take Advantage Of This Growing Market – Meyer Can Get You Started

Need help making your equipment decision or want advice about getting started? We are uniquely qualified to help you profit from the growing demand for insulation removal services. Whether you're an experienced contractor expanding your service offerings or an entrepreneur looking to start a business with great growth potential, we have all the equipment and know-how you need. We can answer all your questions – call us at 888-463-3908 or email us at sales@meyervacuums.com.

PRODUCT SPECIFICATIONS



| | |
|-----------------|---|
| Instrumentation | Optional: Digital Hour Meter, Tachometer, Service Indicator |
| Motor/Engine | 15 HP Kohler OHV with 12 Volt Electric Start and Battery |
| Wheels | 3 (2 pneumatic, 1 swivel caster w/lock) |
| Length | 59" |
| Width | 28" |
| Height | 37" |
| Processing Rate | Cellulose: 4347 cu. ft./hr., 6042 lbs./hr. Fiberglass: 5849 cu. ft./hr., 4199 lbs./hr. |
| Weight | 285 lbs. |

Features & Advantages

- Heavy-gauge, welded steel construction
- Heavy-duty, material-handling fan wheel for years of dependable operation
- Superb handling of wet or dry materials
- 18 month warranty
- Textured, powder-coated finish for long-term protection
- 6" inlet & outlet for greater productivity
- Reduces labor time for increased profitability

For a QUOTE call us at: 1-888-463-3908



Wm. W. Meyer & Sons, Inc.
 1700 Franklin Blvd., Libertyville, IL 60048-4407
 Phone: (800) 797-8227 or (847) 918-0111 | Fax: (847) 918-8183
 Email: sales@meyervacuums.com
 Copyright © 2006. Wm. W. Meyer & Sons, Inc. All rights reserved.