



Temporary Heat For:

- *Construction Sites*
- *Industrial / Commercial Workspaces*
- *Agricultural Buildings*
- *Emergencies*
- *Workshops*
- *Remodeling Jobs*

America's Most Popular Brand Of Portable Heaters!

IT'S THE RIGHT HEAT FOR THE RIGHT JOB.

- **Safe** - Heater shuts off with loss of flame or power supply
- **Instant Heat** - Economical, efficient, and clean burning
- **Maximum Heat Circulation** - Heavy-duty, high output fan
- **Made To Last** - Rugged, durable steel construction
- **Ready To Use** - Simple hook-up; hose and regulator included
- **CSA Certified**
- **Limited 1-Year Warranty**



Temporary Heat For Smaller Jobs

MH35FA

35,000 BTU/HR
F270035

Heats up to 800 square feet. Operates up to 12 hours from a 20 lb. BBQ type propane tank.



MH55FAV

30,000 - 55,000 BTU/HR
F270055

Heats up to 1,250 square feet. Operates up to 14 hours from a 20 lb. BBQ type propane tank on low setting.



MH85FAV

50,000 - 85,000 BTU/HR
F270085

Heats up to 2,000 square feet. Operates up to 8 hours from a 20 lb. BBQ type propane tank on low setting.



Temporary Heat For Larger Jobs

MH125FAV

75,000 - 125,000 BTU/HR
F270125

Heats up to 3,000 square feet. Operates up to 11 hours on a 40 lb. or larger propane tank.



MH170FAVT

125,000 - 170,000 BTU/HR
F270170

Heats up to 4,000 square feet. Operates up to 17 hours on a 100 lb. propane tank.



MH400FAVT

250,000 - 400,000 BTU/HR
F272425

Heats up to 9,000 square feet. Operates up to 17 hours on two, 100 lb. propane tanks on low setting.



	MH35FA	MH55FAV	MH85FAV	MH125FAV	MH170FAVT	MH400FAVT
Stock Number	F270035	F270055	F270085	F270125	F270170	F272425
Output (BTU/HR)	35,000	30,000 - 55,000	50,000 - 85,000	75,000 - 125,000	125,000 - 170,000	250,000 - 400,000
Output CFM	100	300	300	350	450	1400
Fuel	Propane Gas	Propane Gas	Propane Gas	Propane Gas	Propane Gas	Propane Gas
Min. Required Tank Size	20 lb.	20 lb.	20 lb.	40 lb.	100 lb.	100 lb.
Propane Consumption (lbs/hr)	1.6	1.2 to 2.08	2.3 to 3.9	3.5 to 5.8	5.8 to 7.8	11.5 to 18.5
Pressure Regulator Settings	10 PSI	28" W.C.	28" W.C.	28" W.C.	28" W.C.	20 PSI
Adjustable Height Control	-	Yes	Yes	Yes	Yes	-
Flame Safety	Yes	Yes	Yes	Yes	Yes	Yes
High Temperature Limit Switch	240° F	240° F	240° F	240° F	240° F	240° F
Ignition	Piezo	Continuous	Continuous	Continuous	Automatic Solid State	Automatic Solid State
Thermostat	-	-	-	-	Built-in	Built-in
Power Required	115 V. 60 Hz 3a	115 V. 60 Hz 3a	115 V. 60 Hz 3a	115 V. 60 Hz 3a	115 V. 60 4a	115 V. 60 4a
Hose-10ft.	1/4" I.D. w/ Regulator and POL	3/8" I.D. w/ Regulator and POL	3/8" I.D. w/ Regulator and POL	3/8" I.D. w/ Regulator and POL	3/8" I.D. w/ Regulator and POL	1/4" I.D. w/ Regulator and POL
POL/Excess Flow Check Valve	Yes	Yes	Yes	Yes	Yes	Yes
Shipping Size (L x W x H)	19" x 11.5" x 14"	18.5" x 11.5" x 14"	21" x 11.5" x 16"	20.25" x 12" x 15.5"	26.5" x 11.5" x 16.75"	38.58" x 15" x 22.25"
Net Weight (Includes Hose / Regulator / POL Assembly)	15 lbs.	16 lbs.	18 lbs.	23 lbs.	32 lbs.	47 lbs.
Shipping Weight	17 lbs.	20 lbs.	20 lbs.	25 lbs.	34 lbs.	51 lbs.
Shipping Cube	1.8'	1.7'	2.2'	2.7'	3.0'	7.5'