

# Specifications

Model		General Purpose	Recreational	Worksite	Worksite Utility	Turf Utility	
Engine	Make	KUBOTA D902-E2-UV					
	Type	3-cylinders, 4-cycle, diesel, OHV					
	Displacement	cu.in (cc)	54.8 (0.898)				
	Horsepower	HP (kW)/rpm	21.6 (16.1)@3200				
Fuel tank capacity		U.S.gals (ℓ)	7.4 (28)				
Transmission		Variable hydro transmission (VHT)					
Max. Traveling speed		mph (km/h)	25 (40)				
Wheels, drive system		4, 4WD w/2WD selection					
Differential lock		Standard; foot operated with mechanical holder					
Gear selection		Hi-Med-Lo range forward, neutral, reverse					
Brakes	Front / Rear	Wet-disc brake					
	Parking brake	Rear wheel, hand lever					
Steering		Hydrostatic power					
Suspension		Independent, Mac-Pherson strut-type / Semi-independent, DeDion axle w/leaf springs and shock absorbers					
Dimensions	Length	in. (mm)	117.7 (2990)	119.3 (3030)			
	Width	in. (mm)	59.8 (1520)				
	Height, overall	in. (mm)	79.3 (2015)		79.1 (2010)	79.3 (2015)	
	Front tread centers	in. (mm)	45.3 (1150)			46.5 (1180)	
	Rear tread centers	in. (mm)	46.5 (1180)			47.6 (1210)	
	Wheelbase	in. (mm)	77.4 (1965)				
	Ground clearance front/rear axle	in. (mm)	8.3 (210) / 7.5 (190)				
	Turning diameter	ft. (m)	25.6 (7.8)				
Max. rolling weight (Towing capacity)		lbs. (kg)	1300 (590)				
Payload capacity		lbs. (kg)	1653 (750)		1576 (715)		
Weight		lbs. (kg)	1863 (845)	1907 (865)	1918 (870)	1984 (900) / 1995 (905)	
Cargo bed	Width × Length × Depth	in. (mm)	52 (1320) × 46.7 (1180) × 11.4 (290)				
	Volume	cu ft. (m <sup>3</sup> )	16 (0.455)				
	Bed height (unloaded)	in. (mm)	31.5 (800)				
	Cargo bed load	lbs. (kg)	1102 (500)				
Sound level, operator ear		db. (A)	87 @ Max. engine speed w / no load			89 @ Max. engine speed w / no load	
Tires	Front	25×10–12 Knobby, 6PLY	25×10–12 ATV, 6PLY	25×10–12 HDWS, 6PLY	25×10–12 HDWS, 6PLY	25×12–12 Turf, 4PLY	
		25×10–12 HDWS, 6PLY	25×10–12 HDWS, 6PLY	25×10–12 ATV, 6PLY	—	—	
		25×10–12 Turf, 6PLY	—	—	—	—	
	Rear	25×10–12 Knobby, 6PLY	25×11–12 ATV, 6PLY	25×10–12 HDWS, 6PLY	25×10–12 HDWS, 6PLY	25×12–12 Turf, 4PLY	
		25×10–12 HDWS, 6PLY	25×10–12 HDWS, 6PLY	25×10–12 ATV, 6PLY	—	—	
		25×10–12 Turf, 6PLY	—	—	—	—	
Front guard		—	Std.	Std.	Std.	Std.	
Body color		Orange	Camo	Orange	Orange	Orange	
Hydraulic bed lift		—	Std.	Std.	Std.	Std.	
Hydraulic Utility Valve		—	—	—	Std.	Std.	
Speedometer		—	Std.	—	Std.	Std.	

The company reserves the right to change the above specifications without notice. This brochure is for descriptive purpose only. Please contact your local Kubota dealer for warranty and safety information. The values in "Ground clearance" and "Weight" are those of the machine equipped with the tires in the table above. Some RTVs in this brochure are shown with optional accessories. For off-highway use only.