



Quality Tools at Discount Prices

Over 40,000 Hand and Power Tools.

Sales/Info 800-347-5096

Store Hours: M - F: 6:30am - 4:30pm (Pacific Time)

[View Cart](#)

[Manufacturers](#)

[Tool Categories](#)

[Search by Tool Type](#)

[Compare Tools](#)

SEARCH

[Home](#) ▶ [Bosch Tools](#) ▶ [Unishear Shears](#)



Bosch Unishear Shears

BOSCH MODEL 1500C - 16 GAUGE UNISHEAR SHEAR



FEATURES

- | 4.2 Amps, 5,000 SPM
- | Lock-on/off switch for extended use applications
- | Steel deflector for hand protection
- | Compact design slim tool housing comfortably fits in the hand
- | Low vibration for operator comfort
- | Visible blade allows precise pattern cutting extends blade life
- | Easy blade adjustment when switching material thickness
- | Sealed switch keeps debris out of the switch mechanism and extends switch life
- | Epoxy coated field windings provides ultimate protection against metal debris
- | Double Insulated, UL listed, complies to OSHA

SPECIFICATIONS

- | Amperage 4.2
- | Length 7-1/2 In.
- | Weight (lbs.) 4.6
- | Cord Length (ft.) 12
- | Rating 120V AC
- | Cutting Capacity-Aluminum 14 Gauge (.075 In.)
- | Cutting Capacity-Mild Steel 16 Gauge (.060 In.)
- | Cutting Capacity-Stainless Steel 20 Gauge (.036 In.)
- | No Load SPM 5,000
- | Curve Cutting-Minimum Radius 7/8 In.

INCLUDES

- | Blade Set -- 2 608 635 243
- | Feeler Gauge -- 2 607 970 009
- | Allen Wrench 3mm -- 1 907 950 004
- | Steel Deflector -- 3 609 202 083

16 GAUGE UNISHEAR SHEAR

1500C

\$301.50



[Compare to Other Brands](#)

BOSCH MODEL 1506 - 14 GAUGE UNISHEAR SHEAR

FEATURES

- | 4.6 Amps, 2,400 SPM
- | Planetary gear drive more power per pound
- | Upper blade is double-edged when first edge is worn, simply reverse blade
- | Mushroom top handle for extra control under heavy cutting loads easily removed for cutting in confined areas
- | Lightweight and well balanced for excellent control
- | Low vibration for operator comfort
- | Visible blade allows precise pattern cutting



- | Double Insulated, UL listed, complies to OSHA
- | Easy blade adjustment when switching material thickness

SPECIFICATIONS

- | Amperage 4.6
- | Length 10-1/4 In.
- | Weight (lbs.) 6
- | Cutting Capacity-Aluminum .150 In.
- | Engineering Number 0601506134
- | Cord Length (ft.) 12
- | Rating 120V AC
- | Cutting Capacity-Mild Steel 14 (.075 In.)
- | Cutting Capacity-Stainless Steel 16 (.060 In.)
- | No Load SPM 2,400
- | Curve Cutting-Minimum Radius 3/4 In.
- | Category Shears

INCLUDES

- | Upper/Lower Blade Set -- 2 607 010 025
- | 5mm Allen Wrench -- 1 907 950 006

14 GAUGE UNISHEAR SHEAR

1506

\$377.00



Compare to Other Brands

BOSCH MODEL 1507 - 10 GAUGE UNISHEAR SHEAR



FEATURES

- | 8.6 Amps, 1,770 SPM
- | Two-handed control for heavy cutting jobs
- | Top handle with large rocker switch
- | Low vibration for operator comfort
- | Visible blade allows precise cutting
- | Double Insulated, UL listed, complies to OSHA

SPECIFICATIONS

- | Amperage 8.6
- | Length 10 In.
- | Weight (lbs.) 10
- | Cutting Capacity-Aluminum .157 In.
- | Max. Motor HP 0
- | Cord Length (ft.) 0
- | Curve Cutting-Minimum Radius 1 In.
- | No Load SPM 1,770
- | Cutting Capacity-Mild Steel 10G (.135 In.)
- | Rating 120V AC
- | Cutting Capacity-Stainless Steel 12G (.105 In.)

INCLUDES

- | Angled Gauge -- 1 607 970 016
- | Feeler Gauge --1 607 970 015
- | Turning Pin -- 1 607 970 001
- | 5mm Allen Wrench -- 1 907 950 006
- | Upper Blade -- 3 608 635 000
- | Lower Blade -- 3 608 635 002
- | 3mm Allen Wrench -- 1 907 950 004
- | 10mm Open End Wrench -- 1 907 950 504

- | Replacement Upper Blade -- 3 608 635 000
- | Replacement Lower Blade -- 3 608 635 002

COMPARE

Compare to Other Brands

10 GAUGE UNISHEAR SHEAR

1507

\$616.25

 **Add to Cart**

BOSCH MODEL 1508 - 8 GAUGE UNISHEAR SHEAR



FEATURES

- | 9.2 Amps, 1,250 SPM
- | Excellent for high alloy steel cutting
- | Top handle with large rocker switch
- | Low vibration For operator comfort
- | Visible blade Allows precise cutting
- | Auxiliary handle mounts on either side For right- or left-handers
- | Double Insulated, UL listed, complies to OSHA

SPECIFICATIONS

- | Amperage 9.2
- | Length 13.5 In.
- | Weight (lbs.) 15
- | Cutting Capacity-Aluminum .196 In.
- | Max. Motor HP 0
- | Engineering Number 0601508034
- | No Load SPM 1,250
- | Cutting Capacity-Stainless Steel 10G (.135 In.)
- | Cord Length (ft.) 12
- | Rating 120V AC
- | Curve Cutting-Minimum Radius 2 In.
- | Cutting Capacity-Mild Steel 8G (.165 In.)

INCLUDES

- | Angle Gauge -- 1 607 970 016
- | Feeler Gauge -- 1 607 970 015
- | Turning Pin -- 1 607 990 001
- | 5mm Allen Wrench -- 1 907 950 006
- | Upper Blade -- 3 608 635 000
- | Lower Blade -- 3 608 635 002
- | 3mm Allen Wrench -- 1 970 950 004
- | 10mm Open End Wrench -- 1 970 950 504
- | Auxiliary Handle -- 2 602 025 075
- | Replacement Upper Blade -- 3 608 635 000
- | Replacement Lower Blade -- 3 608 635 002

COMPARE

Compare to Other Brands

8 GAUGE UNISHEAR SHEAR

1508

\$1166.00

 **Add to Cart**

[Back to Bosch Index Page](#)



[Home Page](#) | [Milwaukee](#) | [Makita](#) | [Porter-Cable](#) | [etc.](#)



[Homepage](#) | [Tool Search](#) |  [View Cart](#) | [FAX Order](#) | [Tell a Friend](#) | [Contact Us](#)



Sales/Info 800-347-5096 copyright 1997 - 2005 mytoolstore.com by PCT FAX (702) 871-2815