



Call Toll-Free 1-800-553-9053

Quick Search:

Mi-T-M® CORPORATION [Main](#) [About Us](#) [Products](#) [Services](#) [What's New](#) [Contact Us](#)

[▶ Parts Breakdown & Parts Ordering ◀](#)

Products

- ...▶ [Pressure Washers](#)
- ...▶ [Air Compressors](#)
- ...▶ [Wet / Dry Vacuums](#)
- ...▶ [Jobsite Tool Boxes](#)
- ...▶ [Cool Cut® Metal Cutting Saw](#)
- ...▶ [Water Treatment](#)
- ...▶ [Aqueous Parts Washers](#)
- ...▶ [Generators](#)

...▶ [File Library](#)

- ...▶ [Consumer Brochure PDF \(1.1 MB\)](#)
- ...▶ [Mi-T-M Brochure PDF \(29 MB\)](#)
- ...▶ [Generator Brochure PDF \(1.5 MB\)](#)

Product Search

There are two ways to find a product on our site

- » Quick Search: Use the quick search on top of this page
- » Browse: Start at the Product Home Page and browse for tools, accessories, and attachments.

HSP Series - Gasoline - Direct Drive

[Products](#) > [Pressure Washers](#) > HSP Series - Gasoline - Direct Drive

Series Info	Special Features	Options
--------------------	-------------------------	----------------

Challenging applications call for serious equipment. These self-contained, portable gas washers are meant for service centers, automotive shops and other tough cleaning applications.

- Performance-proven OHV engine with low oil protection and recoil start
- Direct drive triplex ceramic piston pump with forged brass manifold
- Thermal relief valve
- Stainless-steel and brass unloader valve
- Low pressure detergent injection
- Complete system diagnostic board
- Pressure and high limit safety controls
- No. 1 or No. 2 diesel or kerosene fired burner
- Polyethylene burner fuel tank
- Temperature rise 150 degrees F/66 degrees C above ambient, maximum 200 degrees F
- Wand holder
- Locking tire brake
- Solid steel threaded axles
- Pneumatic tires with tubes (4)
- 3/8 inch x 50 foot steel wire braided pressure hose with screw connects, swivel, and bend restrictors
- Professional grade insulated trigger gun with safety lock-off
- Adjustable pressure insulated dual lance with 15 degree fixed and detergent nozzle

One (1) year limited parts and labor warranty.
 Three (3) year limited warranty on coil.
 Seven (7) year limited warranty on pump.





MODEL NO.	PSI	GPM	HP	ENGINE	EMF DRIVE	FUEL TANK CAP (GAL)	TANK CAP (GAL)	CONS. (GPH)	UNIT DIM. (LXWXH)	SHIP WT.	SHIP WT.
HSP-2403-3MGH	2400	2.6	6.5	Honda	Belt	0.97	4.0	1.53	38 in. x 30 in. x 38 in.	385 lbs.	269 lbs.
HSP-3003-3MGH	3000	2.9	9.0	Honda	Belt	1.59	5.5	1.84	43 in. x 30 in. x 41 in.	530 lbs.	407 lbs.
HSP-3003-3MGR	3000	2.9	9.0	Subaru	Belt	1.59	5.5	1.84	43 in. x 30 in. x 41 in.	530 lbs.	407 lbs.
HSP-3003-3MGV	3000	2.9	9.0	Vanguard	Belt	1.59	5.5	1.84	43 in. x 30 in. x 41 in.	530 lbs.	407 lbs.
HSP-3004-3MGH	3000	3.5	11.0	Honda	Belt	1.70	5.5	2.14	43 in. x 30 in. x 41 in.	551 lbs.	428 lbs.
HSP-3004-3MGV	3000	3.5	11.0	Vanguard	Belt	1.70	5.5	2.14	43 in. x 30 in. x 41 in.	553 lbs.	430 lbs.
HSP-3504-3MGH	3500	3.3	13.0	Honda	Belt	1.70	5.5	2.14	43 in. x 30 in. x 41 in.	551 lbs.	428 lbs.
HSP-3504-3MGV	3500	3.3	13.0	Vanguard	Belt	1.70	5.5	2.14	43 in. x 30 in. x 41 in.	553 lbs.	430 lbs.

[Main](#) | [About Us](#) | [Products](#) | [Services](#) | [What's New](#) | [Contact Us](#) | [File Library](#)

Copyright © 2006 Mi-T-M Corp., All Rights Reserved.
 8650 Enterprise Drive · Peosta, Iowa 52068 · 1.800.553.9053
 Developed and Maintained by Informatics, Inc.